

CSS Modules with BEM



Questions Tags Users Badges Unanswered Ask Question

Top Questions

interesting

426 featured

hot

week

month

0 votes	0 answers	2 views	How to write code in Swift file that executes when module is loaded?	asked 18 mins ago AttilaTheFun 123
0 votes	3 answers	22 views	showing the div with waste vertical space when I click on the link	modified 18 mins ago Strelok 21.6k
0 votes	0 answers	3 views	Regex Match In Multiple Of n	asked 18 mins ago ryandif 3,571
0 votes	0 answers	18 views	How to start an audio in a specific time without loaded all the file? (like youtube does)	modified 19 mins ago ketan 5,228
0 votes	1 answer	6 views	'user.set' constructed object not a function while testing	modified 19 mins ago realization 65
1 vote	0 answers	27 views	+50 Spark MLlib Kmeans from HDFS	modified 19 mins ago plazaster 32
0 votes	0 answers	2 views	Soundcloud API using SC.get() on private playlist with a secret token	asked 20 mins ago User 8
2 votes	1 answer	11 views	sails.js add a custom task	answered 21 mins ago ovidio4usa 95

Featured on Meta

Upcoming login changes
(Stage 2 now LIVE)

Hot Meta Posts

- When does Community user protect my question?
- Synonym request: [source-code-quality] is just [code-quality]
- Should the bar be raised for Protected Questions?

Favorite Tags edit

mixpanel google-analytics

Looking for a job?

UX Designer

Vigilant Software

Elv, UK / remote

css html

Software Developers - Back-end,
Full-Stack, JavaScript, Scala

Guardian News & Media

London, UK

javascript

amazon-web-services

Consistent Design

Consistent Design

Different Module Versions

Consistent Design

Different Module Versions

Combine Small Modules



Questions Tags Users Badges Unanswered Ask Question

Top Questions

interesting

426 featured

hot

week

month

0 votes	0 answers	2 views	How to write code in Swift file that executes when module is loaded?	asked 18 mins ago AttilaTheFun 123
0 votes	3 answers	22 views	showing the div with waste vertical space when I click on the link	modified 18 mins ago Strelok 21.6k
0 votes	0 answers	3 views	Regex Match In Multiple Of n	asked 18 mins ago ryandif 3,571
0 votes	0 answers	18 views	How to start an audio in a specific time without loaded all the file? (like youtube does)	modified 19 mins ago ketan 5,228
0 votes	1 answer	6 views	'user.set' constructed object not a function while testing	modified 19 mins ago realization 65
1 vote	0 answers	27 views	+50 Spark MLlib Kmeans from HDFS	modified 19 mins ago plazaster 32
0 votes	0 answers	2 views	Soundcloud API using SC.get() on private playlist with a secret token	asked 20 mins ago User 8
2 votes	1 answer	11 views	sails.js add a custom task	answered 21 mins ago ovidio4usa 95

Featured on Meta

Upcoming login changes
(Stage 2 now LIVE)

Hot Meta Posts

- When does Community user protect my question?
- Synonym request: [source-code-quality] is just [code-quality]
- Should the bar be raised for Protected Questions?

Favorite Tags edit

mixpanel google-analytics

Looking for a job?

UX Designer

Vigilant Software

Elv, UK / remote

css html


Software Developers - Back-end,
Full-Stack, JavaScript, Scala

Guardian News & Media

London, UK

javascript

amazon-web-services



Non-modular Naming

```
.tabs {}  
.tab {}  
.active {}
```

```
<ul class="tabs">  
  <li class="tab active">new users</li>  
</ul>
```

reputation

new users

voters

editors

moderators

CSS Selector Nesting

```
.tabs {}  
.tabs .tab {}  
.tabs .tab.active {}
```

```
<ul class="tabs">  
  <li class="tab active">new users</li>  
</ul>
```

reputation

new users

voters

editors

moderators

```
<div class="article">
  <h1 class="title"></h1>

  <div class="photo">
    
    <div class="title"></div>
  </div>
</div>
```

CSS Selector Nesting #2

```
.tabs {}  
.tabs > .tab {}  
.tabs > .tab.active {}
```

```
<ul class="tabs">  
  <li class="tab active">new users</li>  
</ul>
```

reputation

new users

voters


editors

moderators

Block-Element-Modifier (BEM)

```
.tabs {}  
.tabs__tab {}  
.tabs__tab--active {}
```


```
<ul class="tabs">  
  <li class="tabs__tab tabs__tab--active">  
    new users  
  </li>  
</ul>
```




reputation new users voters editors moderators

```
// No styling based on parent
.sidebar .tabs {}
// Instead, use a modifier
.tabs.tabs--sidebar {}
```

	Non-modular Naming	Selector Nesting	BEM
Module structure reflected in CSS	✗	✓	✓
Module structure reflected in HTML	✗	✗	✓
Sibling modules can't override styles	✗	✓	✓
Parent modules can't override styles	✗	✗	✓



```
<ul class="nav nav--vertical list-box">
  <li class="nav__item">
    <a class="nav__item-link">
      Questions
    </a>
  </li>
  <li class="nav__item nav__item--active">
    <a class="nav__item-link">
      Tags
    </a>
  </li>
</ul>
```



```
// Don't style element from another module
.list-box .nav__item {}
// Instead create a new class
.list-box__item {}
<li class="nav__item list-box__item">
    Questions
</li>
```

Format Tools Table Add-ons Help

B Bold ⌘B


I Italic ⌘I

U Underline ⌘U

~~S~~ Strikethrough Option+Shift+5

^{x²} Superscript ⌘.

```
<ul class="menu-bar">
  <li class="menu-bar__item menu-bar__item--active
    menu--active">
    Format
    <ul class="menu__content">
      <li class="menu__item">Bold</li>
      <li class="menu__item">...</li>
    </ul>
  </li>
</ul>
```



Writing BEM in Sass/Less

```
.nav {  
  &__item {  
    color: green;  
    &--active {  
      color: red;  
    }  
  }  
}  
// CSS Output:  
.nav__item { color: green; }  
.nav__item--active { color: red; }
```

Sass ... & feature

```
.a {  
  .b & {...}  
}  
// CSS Output  
.b .a {...}
```


Styling Elements Based on Block Modifiers

```
.nav {  
  &__item {  
    .nav--vertical & {  
      font-size: 20px;  
    }  
  }  
}  
// Generated CSS:  
.nav--vertical .nav__item {  
  font-size: 20px;  
}
```

BEM

Yandex: bem.info

Harry Roberts: [MindBEMding](#) blog post



Thank You

@mattzeunert